



DX (Direct Expansion) Pumping Unit

External Heat Rejection	Max kW Capacity	Max # AHX's	Header Options	Power Options	Full Load Amps (FLA)	ODX Condensing Unit	ODX Power Options	Communication / Monitoring	Heat Exchange	Weight	Dimensions
RPC-020											
Direct Expansion (DX)	20 kW	6	Internal/ External	120-230V, 1Ph, 60HZ	120 VAC: 6A 208 VAC: 3A	ODX-020	208V 1Ph or 3Ph	Modbus/RTU, BACnet/IP, Modbus/TCP-IP	R448A / R449A	375 lbs	15W x 36D x 77.2H
RPC-115											
Direct Expansion (DX)	115 kW (90 kW to 115 kW)	6 or 20	Internal/ External	120-230V, 1Ph, 60HZ	120 VAC: 9A 208 VAC: 5A	ODX-115	480V 3Ph or 240V 3Ph	Modbus/RTU, BACnet/IP, Modbus/TCP-IP	R448A / R449A	400 lbs	15W x 36D x 77.2H
RPC-230											
Direct Expansion (DX)	230 kW	42	External	480V, 3Ph, 60HZ	480VAC: 3A	2x ODX-115	480V 3Ph or 240V 3Ph	Modbus/RTU, BACnet/IP, Modbus/TCP-IP	R448A / R449A	1090 lbs	40W x 36D x 82H

CW (Chilled Water) Pumping Unit

External Heat Rejection	Max kW Capacity	Chilled Water Flow Rate	Chilled Water Supply Temp	Pressure Drop Across the System At Full Open Valve (Max Capacity)	Chilled Water Delta T at Full Load	Max # AHX's	Header Options	Power Options	Full Load Amps (FLA)	Communication / Monitoring	Heat Exchange	Weight	Dimensions
RPW-020													
Chilled Water	20 kW (up to 30kW with higher GPM)	15 GPM	45° F	10 PSI	12° F	6	Internal/ External	120-230V 1Ph, 60HZ	120 VAC: 6A 208 VAC: 3A	Modbus/RTU, BACnet/IP, Modbus/TCP-IP	Chilled water or glycol water	375 lbs	15W x 36D x 77.2H
RPW-115													
Chilled Water	115 kW	60 GPM	45° F	10 PSI	12° F	6 or 20	Internal/ External	120-230V 1Ph, 60HZ	120 VAC: 9A 208 VAC: 5A	Modbus/RTU, BACnet/IP, Modbus/TCP-IP	Chilled water or glycol water	400 lbs	15W x 36D x 77.2H
RPW-210													
Chilled Water	210 kW	120 GPM	45° F	20 PSI	12° F	42	External	480V 3Ph, 60HZ	480VAC: 3A	Modbus/RTU, BACnet/IP, Modbus/TCP-IP	Chilled water or glycol water	1030 lbs	40W x 36D x 82H

*Water capacity ratings and flow rates do not include glycol in water